

Manufactured By:

HILARK

MONGOOSE

MONGOOSE DUMP BODY



Some equipment shown is optional.
See dealer for additional information on
optional equipment.

**DESIGNED FOR ROCK, BROKEN CONCRETE,
DEMOLITION AND OTHER HIGH-IMPACT
JOBS THE OTHERS BACK AWAY FROM**

**FEATURES OPTIONAL AR-450 FRONT,
DOGHOUSE, BODY AND GATE**

**AVAILABLE IN 3/16, 1/4 & 5/16 THICKNESS
WITH OR WITHOUT CROSSMEMBERS**


HilBilt
DUMP BODIES



RIGID UNDERBODY

The understructure is manufactured with an 8"x 2" x 1/4" tube main frame, 6"x 4"x 10 gauge channel crossmembers on 12" centers.

Crossmembers are solid welded on each side to the floor and main frame.



MOUNTING SADDLE & HYDRAULIC TANK

Fabricated on site with industry leading quality control standards.

CAB PROTECTOR

Features angle bracing for maximum strength. Options include 1/4, 1/2, 3/4 & Full. Shown with optional integrated tarp mount.

MONGOOSE



SIDE TOP RAIL

Standard 6"x 4" rectangular tube providing additional strength and rigidity versus a formed section top rail.


PARKER HEAVY-DUTY TELESCOPING HYDRAULIC HOIST

1-15/16" x 13" cylinder pin is standard.



UPPER TAILGATE HINGE

Built of 3/4" AR-450 steel hinge arms, 3/8" Hi-Tensile steel side plates, three case-hardened bushings and a removable pin designed to grease all three bushings ensuring longer life and easier maintenance.



TAILGATE LATCH ASSEMBLY

Constructed with a 5/8" AR-200 steel latch arm, five grease pivot points and operated with a 3.5" double-acting air cylinder. Remains closed even in case of air malfunction.



REAR HINGE

Standard 1-15/16" Hinge Pin with 1/2" wall greaseable bushings.

Some equipment shown is optional. See dealer for complete details

Manufactured By:

HilArk Industries
20020 Interstate 30
Benton, AR 72019
Ph: (501) 316-4040
Fax: (501) 634-4141
www.hilark.com



Authorized
Distributor:

